

TECHNICAL DATA SHEET



CURB RAMP

PRODUCT AND COMPANY IDENTIFICATION

| | |
|-----------------------------|---|
| Product name: | CURB RAMP |
| Uses: | Rubber curb ramp. |
| Supplier: | FIXER PAVIMENTOS TÉCNICOS, S.L. P.I. "LA MUNTANYA" Parcelas 44 y 45 46293-BENEIXIDA (VALENCIA). Tel: +34962976630 administracion@fixer.es |
| Emergency telephone: | +34 91 562 04 20 National Institute of Toxicology. |

Description


Curb ramp in recycled rubber with yellow rubber bands integrated in the piece by vulcanization. Ecological product. Respectful of the environment. Soundproofing when vehicles pass by.

It is a solid product, very resistant to the passage of vehicles, even heavy ones. It is adjustable with its supplements in four heights 8, 10, 12 and 14 cm.

Highly robust, shock absorbing, highly resistant to abrasion, ozone and UV rays.

Technical specifications

- **Dimensions:** length: 50 cm, width: 32 cm.
- **Anchoring system:** 4 screws and 4 plugs (supplied).



| TEST | UNITS | VALUES |
|---------------------|-------------------|--------|
| Hardness | ° Shore A | 79 |
| Density | g/cm ³ | 1.23 |
| Abrasion resistance | mm ³ | 184 |
| Traction resistance | % | 4.1 |
| Elongation | % | 108 |
| Rip resistance | kN/m | 8.3 |