

# TECHNICAL DATA SHEET



**PAINT-FIX SPORT**

**PRDV06000/1**

## PRODUCT IDENTIFICATION AND COMPANY

<b>Product name:</b>	<b>PAINT-FIX SPORT</b>
<b>Uses:</b>	PAINTING FOR SPORTS TRACKS
<b>Supplier:</b>	FIXER PAVIMENTOS TECNICOS, S.L. P.I. "La Muntanya" Parcelas 44 y 45 46293 - Beneixida (Valencia) Tel: +34 96 297 66 30 administracion@fixer.es
<b>Emergency telephone:</b>	+34 91 562 04 20 National Institute of Toxicology

### Description

**PAINT-FIX SPORT** is a monocomponent acrylic paint based on synthetic, plasticizers and inert resins, indicated for the painting of pavements of medium stresses and sealing of slurries.

### Characteristics

- Non-toxic, non-flammable product.
- Good adhesion to asphalt agglomerate surfaces, slurries and porous concretes.
- Easy to apply and quick drying.
- Good resistance to abrasion and microcracks.
- Resistant to the fall of fuels.

### Uses

- Parking, garage and recreational areas.
- Sealing of slurries in bicycle lanes, hard shoulders, islets, signs, sidewalks ...

### Application

#### Surface preparation:

Surface must be clean of dust, grease, oil and any other foreign material, as well as having an adequate mechanical resistance and sufficient porosity to ensure the adherence of the product.

#### Handling:

The product is ready for use. Homogenize in its packaging before application, adding if necessary, a small amount of water, up to 5%.

Paving in thin layers, using a roller or airless gun, at a rate of approximately 350 to 400 g/m<sup>2</sup> per layer, waiting for the first layer to be completely dry before applying the next one when necessary. The drying time depends on the temperature and humidity of the environment, being from 4 to 5 hours at 25 °C.

### Precautions

- Do not apply the product in rainy weather.
- The ambient temperature for application and curing will be between 10 and 30 °C.

### Packaging and storage

**PAINT-FIX SPORT** is supplied in 25 kg plastic buckets.

Standard colors: red, green, grey, black, blue and albero.

Other colors: consult availability.

## TECHNICAL DATA SHEET



**PAINT-FIX SPORT**

**PRDV06000/1**

It must be stored in its original packaging, in a dry place, protected from frost and direct sunlight. Temperatures below 5°C may affect product quality.

Its lifespan is 24 months from production date, properly preserved.



### LEGAL NOTICE

This information, and in particular the recommendations regarding the application and final use of the product, are based on Fixer's experience and knowledge, when the product has been applied and handled within the limits described in the current data sheet. If the environmental conditions of temperature and humidity, or the support conditions change, they may lead to differences in the data indicated in this technical sheet. For this reason, it is not deductible of the information of the present document, of any other written recommendation, or of any offered advice, any guarantee or obligation outside of any legal relation that could exist. Customers and users must know and use the latest and updated version of the Product Data Sheets, a copy of which will be sent to anyone who requests them.