



PRODUCTS

TP-Fix





# TP-Fix

Thermostable resin

It is a thermostable bi-component resin of rapid hardening for fixing casting elements to the roadway (grids, manhole covers, scuppers, etc...) with immediate restoration of heavy traffic.

No traffic cut-off required.

## Technical data sheet:

### Characteristics

Prevents the collapse, cracking and chronic deterioration of casting elements. It can be used in any season of the year (rain, snow, very resistant to frost, abrasion and salt treatment), even with temperatures below 0°C and on wet concrete support.

Quick and easy to use.

No mixing tools, no water, and no electricity are required at the construction site.

Achieves high resistance to compression and bending in a short time frame.

### Conservation

Keep the product stored between +5°C and 25°C, maximum 12 months.

### Resistance

Mechanical resistance (after 1 hour): COMPRESSION: 815 Kg/cm<sup>2</sup>  
 – BENDING STRESS: 360 Kg/cm<sup>2</sup>.

### Sales format

25 kg pack (24 Kg Component A + 1 Kg Component B). Pallet 36 container..

### Indicative drying

TEMPERATURE °C	30	25	20	15	10	5	0	-5	-10
TIME (MINUTES)	5	8	10	15	20	25	30	35	45

### Application/User guide



### Steps to follow



Remove the sewer cover



Formwork



TP-FIX application



Finish with asphalt